

MDrive[®] Plus

Stepper motors with integrated electronics



MDrive 34 Plus Speed Control
with programmable velocity control



MDrive® Plus Speed Control with programmable velocity control

Presentation

The MDrive® Plus Speed Control with programmable velocity control is a 1.8° 2-phase stepper motor with on-board control electronics. The velocity control uses voltage, current, or PWM analog input signal modes.

Settings for MDrive Plus Speed Control products may be changed on-the-fly or downloaded and stored in nonvolatile memory using the IMS SPI Motor Interface software provided. This eliminates the need for external switches or resistors. Parameters are changed via an SPI port.

Application areas

The MDrive Plus Speed Control with programmable velocity control is ideal for machine builders who want an optimized motor with on-board electronics. The integrated electronics of the MDrive Plus Speed Control with programmable velocity control reduces the potential for problems due to electrical noise by eliminating the cable between motor and drive.

These compact, powerful and cost effective motion control solutions deliver unsurpassed smoothness and performance that will reduce system cost, design and assembly time for a large range of 2-phase stepper motor applications.

Features

- Highly integrated microstepping drive and high torque 1.8° 2-phase stepper motor
- Advanced current control for exceptional performance and smoothness
- Single supply: from +12 up to +75 VDC
- Cost effective
- Extremely compact
- 20 microstep resolutions up to 51,200 steps per rev including: Degrees, Metric, Arc Minutes
- 10-bit analog speed control inputs accept:
 - 0 to +5 VDC
 - 0 to +10 VDC
 - 4 to 20 mA
 - 0 to 20 mA
 - 15 to 25 kHz PWM
- Automatic current reduction
- Electronically configurable:
 - Motor run/hold current
 - Microstep resolution
 - Acceleration/deceleration
 - Initial and maximum velocity
 - Hold current delay time/motor settling delay time
 - Programmable filtering for the stop/start input
- Available options:
 - Encoder
 - Control knob for manual positioning
- Several motor stack lengths available
- Setup parameters may be switched on-the-fly
- Numerous connector interface choices
- Graphical user interface provided for quick and easy parameter setup

MDrive[®] Plus Speed Control with programmable velocity control

Plus specifications

		MDrive 17	MDrive 23 (1)	MDrive 23 (1)	MDrive 34
Input power	Voltage	12 to 48	12 to 75	12 to 60	12 to 75
	Current maximum (2)	2A	2A	3.5A	4A
Thermal	Operating temp non-condensing	-40° to +85°C			-40° to +75°C
	Heat sink	-40° to +100°C			-40° to +90°C
Speed control	Input	0 to +5 VDC (4), 0 to +10 VDC, 4 to 20 mA, 0 to 20 mA, or 15 to 25 kHz PWM			Speeds A1 and A2: 0 to +5 VDC (4), 0 to +10 VDC, 4 to 20 mA, or 0 to 20 mA
	A/D resolution	10 bit			10 bit
Logic input	Low level	0 to +0.8 VDC			0 to +0.8 VDC
	High level	+2.0 to +5.0 VDC			+5.0 to +24.0 VDC
	Internal pull-up resistance	20 kΩ (to +3.3 VDC)			not applicable
	Optically isolated	no			yes
	Configurable	sinking			sourcing or sinking
Logic output	Step clock / direction	Open drain source maximum	not applicable		+100 VDC
		Open drain current continuous	not applicable		100 mA
		Output pulse width	not applicable		100 nSec to 12.8 μSec software configurable
Motion	Oscillator frequency maximum	5 MHz			
	Microstep resolution	Number of settings	20		
		Steps per revolution	200, 400, 800, 1000, 1600, 2000, 3200, 5000, 6400, 10000, 12800, 20000, 25000, 25600, 40000, 50000, 51200, 36000 (0.01 deg/μstep), 21600 (1 arc minute/μstep), 25400 (0.001mm/μstep)		

Setup parameters (4)

SPI communication	Function	Range	Units	Default
A1 (5)	Analog input mode	0 to +5 VDC, 0 to +10 VDC, 4 to 20 mA, 0 to 20 mA, or 15 to 25 kHz PWM	—	0 to +5 VDC
ACCL	Acceleration	91 to 1.5 X 10 ⁹	steps/sec ²	1,000,000
C (7)	Joystick center	1 to 1022	counts	0
CLK OUT (6)	Clock out	none, step/dir, quadrature, up/down	—	none
DB (8)	Analog deadband	0 to 255	counts	1
DECL	Deceleration	91 to 1.5 X 10 ⁹	mSec	500
DIR	Motor direction override	Clockwise (cw)/counterclockwise (ccw)	—	cw
FAULT	Fault/checksum error	error code	—	none
FS (8)	Analog full scale	1 to 1023	counts	1023
HCDT	Hold current delay time	HCDT + MSDT <= 65535	milliseconds	500
IF (8)	Analog input filter	1 to 1000	counts	1
	Source	A1 spd/A2 spd or PWM 15 to 25 kHz	—	A1&A2
IMODE (6)	Analog input, A1&A2 spds	0 to +5 VDC, 0 to +10 VDC, 4 to 20 mA, 0 to 20 mA	volts or current	0 to +5 VDC
	Motor hold current	0 to 100	percent	5
MRC	Motor run current	1 to 100	percent	25
MSDT	Motor settling delay time	MSDT + HCDT <= 65535	milliseconds	0
MSEL	Microstep resolution	1, 2, 4, 5, 8, 10, 16, 25, 32, 50, 64, 100, 108, 125, 127, 128, 180, 200, 250, 256	μsteps per full step	256
STEPW (6)	Step width	0 (square wave), 100 nSec to 12.8 μSec	nSec	550 nSec
SSD	Stop/start debounce	0 to 255	milliseconds	0
VI	Initial velocity	0 to <VM	steps/sec	1000
VM	Maximum velocity	VI to 5,000,000	steps/sec	768,000
TEMP (6)	Warning temperature	0 to 85°C	°C	80°C
USER ID	User ID	customizable	1-3 characters	IMS

(1) Only quad stack NEMA 23 motors have +12 to +60 VDC drives, all other NEMA 23 motors have +12 to +75 VDC drives.

(2) Adjusting the microstep resolution can increase the range.

(3) 10 kΩ potentiometer resistance.

(4) All parameters are set using the supplied IMS SPI Motor Interface GUI and may be changed on-the-fly. An optional Communication Converter is recommended with first orders.


(5) Only with MDrive17 & MDrive23 products.

(6) Only with MDrive34 products.

(7) Separate analog inputs for A1 and A2 speeds with MDrive 34 products.




– Plus – mechanical specifications, dimensions in inches (mm)



Motor stack length	L _{max} (1)	L _{max2} (2)
Single	3.81 (96.77)	4.52 (114.81)
Double	4.60 (116.84)	5.31 (134.87)
Triple	6.17 (156.72)	6.88 (174.75)


(1) Single shaft or internal encoder.
 (2) Control knob.

Connector options




Pluggable interface version:
 12-pin* and 2-pin locking and
 10-pin friction lock wire crimp
 connectors

* 12-pin replaced by 20-pin
 locking wire crimp connector
 when optional internal encoder
 is included



Flying leads interface version:
 12" (305mm) flying leads with
 10-pin non-locking IDC connector

L_{max2} option








control knob

MDrive® 34 Plus

Speed Control

with programmable velocity control



Installation accessories

Description	Length feet (m)	Part number
-------------	-----------------	-------------

QuickStart Kit

For rapid design verification, all-inclusive QuickStart Kits include connectivity, instructions and CD for MDrive Plus initial functional setup and system testing.

- For all MDrive34 Speed Control products. — add "K" to part number (1)

Communication converter

Electrically isolated, in-line converter pre-wired with mating connector to conveniently set/program communication parameters for a single MDrive Plus via a PC's USB port.

- | | | |
|------------------------------------------------------|------------|--------------|
| ■ Mates to 10-pin non-locking IDC connector | 12.0 (3.6) | MD-CC300-001 |
| ■ Mates to 10-pin friction lock wire crimp connector | 12.0 (3.6) | MD-CC302-001 |

Prototype development cable

Speed test/development with pre-wired mating connector with other cable end open.

- | | | |
|--------------------------------------------------------------------------------------|------------|----------------|
| ■ Mates to 12-pin locking wire crimp connector for I/O and optional internal encoder | 10.0 (3.0) | PD12B-2334-FL3 |
| ■ Mates to 20-pin locking wire crimp connector for I/O and remote encoder option | 10.0 (3.0) | PD20B-3400-FL3 |
| ■ Mates to 2-pin locking wire crimp connector for power | 10.0 (3.0) | PD02-3400-FL3 |

Mating connector kit

Connectors for assembly of cables, cable material not supplied. Sold in lots of 5. Manufacturer's crimp tool recommended for crimp connectors.

- | | | |
|-----------------------------------------------------------------------------|---|-------|
| ■ 10-pin non-locking IDC connector for communication | — | CK-01 |
| ■ 10-pin friction lock wire crimp connector for communication | — | CK-02 |
| ■ 12-pin locking wire crimp connector for I/O and optional internal encoder | — | CK-08 |
| ■ 20-pin locking wire crimp connector for I/O and remote encoder option | — | CK-11 |
| ■ 2-pin locking wire crimp connector for power | — | CK-05 |

Drive protection module


Limits surge current and voltage to a safe level when DC input power is switched on-and-off to an MDrive Plus.

- | | | |
|-------------------------------------------|---|-------|
| ■ For all MDrive34 Speed Control products | — | DPM75 |
|-------------------------------------------|---|-------|

(1) See next page.


MDrive® 34 Plus Speed Control with programmable velocity control

MDrive® 34 Plus²
flying leads interface



- P1: I/O & Power**
F = 12" flying leads
- P2: Communication**
D = SPI with 10-pin IDC non-locking connector

MDrive® 34 Plus²
pluggable interface



- P1: I/O and optional encoder**
C = 12-pin locking wire crimp connector (20-pin with internal encoder option)
- P3: Power**
2-pin locking wire crimp connector
- P2: Communication**
L = 10-pin friction lock wire crimp connector

Part numbers												
Example:	K	M	D	O	3	F	S	D	3	4	A	7 -E1
QuickStart Kit K = kit option, or leave blank if not wanted	K	M	D	O	3	F	S	D	3	4	A	7 -E1
MDrive Plus version MDO = Speed Control	K	M	D	O	3	F	S	D	3	4	A	7 -E1
Input 3 = Plus ² , expanded features	K	M	D	O	3	F	S	D	3	4	A	7 -E1
P1 connector F = flying leads C = pluggable	K	M	D	O	3	F	S	D	3	4	A	7 -E1
Communication S = SPI	K	M	D	O	3	F	S	D	3	4	A	7 -E1
P2 connector D = only with P1 connector F L = only with P1 connector C	K	M	D	O	3	F	S	D	3	4	A	7 -E1
Motor size 34 = NEMA 34 (3.4" / 86 mm)	K	M	D	O	3	F	S	D	3	4	A	7 -E1
Motor length A = single stack B = double stack C = triple stack	K	M	D	O	3	F	S	D	3	4	A	7 -E1
Drive voltage 7 = +12 to +75 VDC	K	M	D	O	3	F	S	D	3	4	A	7 -E1
Options Leave blank if not wanted Options may be combined												-E1
-E___ = internal optical encoder with index mark (1)												
	line count	100	200	250	256	400	500	512	1000	1024		
	single-end part #	E1	E2	E3	EP	E4	E5	EQ	E6	ER		
	differential part #	EA	EB	EC	EW	ED	EH	EX	EJ	EY		
-N = rear control knob for manual positioning												

(1) Products with pluggable interface available only with differential encoder.



Easy MDrive part numbers via an interactive tool at:
www.imshome.com/MDrivePlus.html

MDrive[®] 34 Plus

Speed Control


with programmable velocity control

Motor specifications MDrive 34


		Holding torque	Detent torque	Rotor inertia	Weight (motor + driver)
Motor stack length	Single	381.0 oz-in / 269.0 N-cm	10.9 oz-in / 7.7 N-cm	0.01416 oz-in-sec ² / 1.0 kg-cm ²	4.1 lb / 1.9 kg
	Double	575.0 oz-in / 406.0 N-cm	14.16 oz-in / 10.0 N-cm	0.02266 oz-in-sec ² / 1.6 kg-cm ²	5.5 lb / 2.5 kg
	Triple	1061.0 oz-in / 749.0 N-cm	19.83 oz-in / 14.0 N-cm	0.04815 oz-in-sec ² / 3.4 kg-cm ²	8.8 lb / 4.0 kg

Speed torque characteristics MDrive 34


Single stack length



Double stack length



Triple stack length



USA SALES OFFICES

Eastern Region

Tel. 862 208-9742 - Fax 973 661-1275
e-mail: e.region@imshome.com

Northeast Region

Tel. 860 368-9703
e-mail: n.region@imshome.com

Central Region

Tel. 860 295-6102
e-mail: c.region@imshome.com

Western Region

Tel. 602 578-7201
e-mail: w.region@imshome.com

IMS EUROPEAN SALES MANAGEMENT

4 Quai Des Etroits
69005 Lyon, France
Tel. +33/4 7256 5113 - Fax +33/4 7838 1537
e-mail: europa.sales@imshome.com

TECHNICAL SUPPORT

Tel. +00 (1) 860 295-6102 - Fax +00 (1) 860 295-6107
e-mail: etech@imshome.com

Schneider Electric Motion USA

370 North Main Street, P.O. Box 457
Marlborough, CT 06447 - U.S.A.
Tel. +00 (1) 860 295-6102 - Fax +00 (1) 860 295-6107
e-mail: info@imshome.com
www.schneider-electric-motion.us